



**MATERIAL SAFETY DATA  
SHEET**

(Page 1 of 2)

---

200 Bouchard Street Manchester, NH 03103 PHONE: (603) 296-2221 FAX: (603) 296-2248 [www.textilescoated.com](http://www.textilescoated.com)

---

**TEX-LFP 14-20 Flue Duct Seal Product**

**Section I**

Manufacturer: Textiles Coated Incorporated  
200 Bouchard Street  
Manchester, NH 03103

General Description: Fluoropolymer/fiberglass fabric laminate

---

**Section II --- Ingredients**

<u>Ingredients</u>	<u>Percent</u>
Fluoroplastic polymer	62
Fiberglass fabric	38

---

**Section III --- Health Hazard Data**

Effects of exposure: May be a skin irritant if product is severely damaged.

First aid procedures: Wash affected area with soap and water.

---

**Section IV --- Fire and Explosion Data**

Autoignition point: 900 °F

Extinguishing media: Water

Special fire fighting protective equipment: Self-contained breathing apparatus with full facepiece and protective clothing if involved in a fire of other materials.

Unusual fire and explosion hazards: Product will emit toxic fumes at high temperatures.

---

January 1, 2011



**MATERIAL SAFETY DATA  
SHEET**

(Page 2 of 2)

---

200 Bouchard Street Manchester, NH 03103 PHONE: (603) 296-2221 FAX: (603) 296-2248 [www.textilescoated.com](http://www.textilescoated.com)

---

**TEX-LFP 14-20 Flue Duct Seal Product**

**Section V ---  
Physical Data**

Boiling point: None  
Specific gravity: 2.3  
Softening point: Not applicable  
Melting point: Not applicable  
Vapor density: Not applicable  
Percent volatile: Not applicable  
Evaporation rate: Not applicable  
Solubility in water: Not applicable  
Odor-appearance-color: black/gray or brown, odorless, fabric

---

**Section VI --- Reactivity Data**

Stability: Stable  
Incompatibility (material to avoid): Fabric strength is destroyed in strong bases and hydrofluoric acid.  
Hazardous decomposition products: Traces of incompletely burned fluorocarbon products.  
Hazardous polymerization will not occur.

---

**Section VII --- Spill and Disposal Procedures**

Material can be brushed off, rerolled, and used.  
Waste disposal procedure: Land fill compliance with local, state, and federal regulations.

---

**Section VIII --- Personnel Protection Information**

Normal long sleeved work clothing and gloves should be worn.  
Lifting devices may be needed for heavy rolls.  
Wash work clothes separately from other clothing.  
Ventilation: - Local exhaust - None  
                  - Mechanical (general) - Recommended

---

**TEX-LFP** is a trademark of **TEXTILES COATED INCORPORATED**.

This information is supplied in good faith and is based on information currently available. TCI makes NO WARRANTIES, EITHER EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTIES FOR FITNESS, OR USE FOR A PARTICULAR PURPOSE, OR OF ANY MERCHANTABILITY OR AGAINST INFRINGEMENT OR THE LIKE, unless expressly set forth herein.

January 1, 2011