

PO Box 532/105 Rt. 101A Amherst, NH 03031 (603) 883-9932 FAX (603) 883-9956 www.textilescoated.com

## **THERMALAM 50/1406 Expansion Joint Product**

### **Section I**

Manufacturer: Textiles Coated Incorporated  
PO Box 532  
105 Rt. 101A.  
Amherst, NH 03031

General Description: Fluoropolymer/fiberglass fabric laminate

---

### **Section II --- Ingredients**

<u>Ingredients</u>	<u>Percent</u>
Fluoroplastic polymer	29
Fiberglass fabric/mat	71

---

### **Section III --- Health Hazard Data**

ACGIH TLV is 10 mg/cu mtr total dust. OSHA considers fibrous glass dust a nuisance. Effects of exposure: Skin, eye, and respiratory tract irritation by contact with dust and fiber are effects associated with all forms of fibrous glass.

Fist aid procedures: Eye contact - Flush with water for 15 minutes - get medical assistance if condition persists. Skin contact - Wash affected area with soap and water. Inhalation - Remove to fresh air.

---

### **Section IV --- Fire and Explosion Data**

Autoignition point: NA

Extinguishing media: Water

Special fire fighting protective equipment: Self-contained breathing apparatus with full facepiece and protective clothing if involved in a fire of other materials.

Unusual fire and explosion hazards: Product will emit toxic fumes at high temperatures.

**THERMALAM 50/1406 Expansion Joint Product**

**Section V ---**

**Physical Data**

Boiling point: None  
Specific gravity: 2.4  
Softening point: Not applicable  
Melting point: Not applicable  
Vapor density: Not applicable  
Percent volatile: Not applicable  
Evaporation rate: Not applicable  
Solubility in water: Not applicable  
Odor-appearance-color: brown/white, odorless, fabric

**Section VI --- Reactivity Data**

Stability: Stable  
Incompatibility (material to avoid): Fabric strength is destroyed in strong bases and hydrofluoric acid.  
Hazardous decomposition products: Traces of incompletely burned fluorocarbon products. Hazardous polymerization will not occur.

**Section VII --- Spill and Disposal Procedures**

Material can be brushed off, rerolled, and used.  
Waste disposal procedure: Land fill compliance with local, state, and federal regulations.

**Section VIII --- Personnel Protection Information**

Normal long sleeved work clothing and gloves should be worn.  
Lifting devices may be needed for heavy rolls.  
Wash work clothes separately from other clothing.  
Gloves and barrier creams if necessary. Safety glasses with side shields/safety goggles.  
Approved air supplied or self-contained respirator for nonroutine or emergency situation.  
Where dust is uncontrolled, use NIOSH approved dust respirator.  
Ventilation: - Local exhaust - Where dust generation is apparent  
- Mechanical (general) - Recommended

**THERMALAM** is a trademark of **TEXTILES COATED INCORPORATED**.

This information is supplied in good faith and is based on information currently available. TCI makes NO WARRANTIES, EITHER EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTIES FOR FITNESS, OR USE FOR A PARTICULAR PURPOSE, OR OF ANY MERCHANTABILITY OR AGAINST INFRINGEMENT OR THE LIKE, unless expressly set forth herein.

August 1, 2007