



TUFJAC 1550 Description: This Silicone/fiberglass composite has a rugged coating technology that is engineered for removable pads, flanges and valve covers.

- ⇒ **Successfully used in insulation jacketing applications since 1985.**
- ⇒ **Incorporates rugged TUFJAC coating technology.**
- ⇒ **Severe temperature and chemical exposure capability.**
- ⇒ **Flame retardant.**
- ⇒ **Easily sewn.**
- ⇒ **Variations engineered upon request.**

TUFJAC 1550 Properties:

<i>Upper Use Temperature:</i>	480°F (249°C) Continuous Service.
<i>Weight:</i>	15.5 oz/yd ² (526 g/m ²)
<i>Thickness:</i>	0.016" (0.41 mm)
<i>Width:</i>	60" (1524 mm) Nominal
<i>Tensile Strength (Warp):</i>	370 lbs/in (3307 N/50 mm)
<i>Tensile Strength (Fill):</i>	310 lbs/in (2770 N/50 mm)

TUFJAC is a trademark of **TEXTILES COATED INCORPORATED**.

This information is supplied in good faith and is based on information currently available. TCI makes NO WARRANTIES, EITHER EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTIES FOR FITNESS, OR USE FOR A PARTICULAR PURPOSE, OR OF ANY MERCHANTABILITY OR AGAINST INFRINGEMENT OR THE LIKE, unless expressly set forth herein.