



**Product Close-up**

**TUFJAC 1725 Description: This Silicone/ fiberglass composite has a rugged coating technology that is engineered for removable pads, flanges and valve covers.**

- ⇒ **Successfully used in insulation jacketing applications since 1985.**
- ⇒ **Incorporates rugged TUFJAC coating technology.**
- ⇒ **Severe temperature and chemical exposure capability.**
- ⇒ **Flame retardant.**
- ⇒ **Easily sewn.**
- ⇒ **Variations engineered upon request.**

## **TUFJAC 1725 Properties:**

<b><i>Upper Use Temperature:</i></b>	480°F (249°C) Continuous Service.
<b><i>Weight:</i></b>	17 oz/yd <sup>2</sup> (577 g/m <sup>2</sup> )
<b><i>Thickness:</i></b>	0.017" (0.43 mm)
<b><i>Width:</i></b>	60" (1524 mm) Nominal
<b><i>Tensile Strength (Warp):</i></b>	370 lbs/in ( 3307 N/50 mm)
<b><i>Tensile Strength (Fill):</i></b>	310 lbs/in ( 2770 N/50 mm)

**TUFJAC** is a trademark of **TEXTILES COATED INCORPORATED.**

This information is supplied in good faith and is based on information currently available. TCI makes NO WARRANTIES, EITHER EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTIES FOR FITNESS, OR USE FOR A PARTICULAR PURPOSE, OR OF ANY MERCHANTABILITY OR AGAINST INFRINGEMENT OR THE LIKE, unless expressly set forth herein.