



**Product Close-up**

***TEXCOAT 100* Description:** This PTFE/fiberglass composite is designed for flexible expansion joint applications.

- ⇒ **Successfully used in expansion joint service since 1985.**
- ⇒ **Incorporates proven *TEXCOAT* coating technology for industrial fabrication.**
- ⇒ **Severe chemical and temperature exposure capabilities.**
- ⇒ **Variations engineered upon request.**



**Many  
Colors  
Available**

***TEXCOAT 100* Properties:**

<b><i>Upper Use Temperature:</i></b>	600°F (316°C) Continuous Service
<b><i>Weight:</i></b>	13 oz/yd <sup>2</sup> (441.00 g/m <sup>2</sup> )
<b><i>Thickness:</i></b>	0.009" (0.23 mm)
<b><i>Width:</i></b>	36" (914.4 mm) Typical; Cut-to-Size widths available.
<b><i>Tensile Strength (Warp):</i></b>	250 lbs/in (2234 N/50 mm)
<b><i>Tensile Strength (Fill):</i></b>	200 lbs/in (1787 N/50 mm)

***TEXCOAT*** is a trademark of **TEXTILES COATED INCORPORATED.**

This information is supplied in good faith and is based on information currently available. TCI makes NO WARRANTIES, EITHER EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTIES FOR FITNESS, OR USE FOR A PARTICULAR PURPOSE, OR OF ANY MERCHANTABILITY OR AGAINST INFRINGEMENT OR THE LIKE, unless expressly set forth herein.