



Product Close-up

***TEXCOAT 300* Description:** This PTFE/ fiberglass composite is designed for flexible expansion joint applications.

- ⇒ **Successfully used in expansion joint service since 1985.**
- ⇒ **Incorporates proven *TEXCOAT* coating technology for industrial fabrication.**
- ⇒ **Severe chemical and temperature exposure capabilities.**
- ⇒ **Variations engineered upon request.**



**Many
Colors
Available**

***TEXCOAT 300* Properties:**

<i>Upper Use Temperature:</i>	600°F (316°C) Continuous Service
<i>Weight:</i>	19 oz/yd ² (644 g/m ²)
<i>Thickness:</i>	0.014" (0.36 mm)
<i>Width:</i>	60" (1524 mm) Nominal
<i>Tensile Strength (Warp):</i>	325 lbs/in (2904 N/50 mm)
<i>Tensile Strength (Fill):</i>	275 lbs/in (2457 N/50 mm)

TEXCOAT is a trademark of **TEXTILES COATED INCORPORATED.**

This information is supplied in good faith and is based on information currently available. TCI makes NO WARRANTIES, EITHER EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTIES FOR FITNESS, OR USE FOR A PARTICULAR PURPOSE, OR OF ANY MERCHANTABILITY OR AGAINST INFRINGEMENT OR THE LIKE, unless expressly set forth herein.