



Product Close-up

TEXTIFILM 704 Description: **TEXTIFILM 704** is engineered for dry, gas seal service. A 0.004" (0.1 mm) PTFE film is laminated to the **TEXCOAT 700** product.

- ⇒ **Successfully used in expansion joint service since 1990.**
- ⇒ **Proven coating and lamination technology for industrial fabrication.**
- ⇒ **Severe chemical and temperature exposure capabilities.**
- ⇒ **Variations engineered upon request.**



**Many
Colors
Available**

TEXTIFILM 704 Properties:

Upper Use Temperature: 600°F (315°C) Continuous Service

Weight: 38 oz/yd² (1289 g/m²)

Thickness: 0.034" (0.86 mm)

Width: 58" (1473 mm) Nominal

Tensile Strength (Warp): 700 lbs/in (6256 N/50 mm)

Tensile Strength (Fill): 700 lbs/in (6256 N/50 mm)

TEXTIFILM is a trademark of **TEXTILES COATED INCORPORATED**.

This information is supplied in good faith and is based on information currently available. TCI makes NO WARRANTIES, EITHER EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTIES FOR FITNESS, OR USE FOR A PARTICULAR PURPOSE, OR OF ANY MERCHANTABILITY OR AGAINST INFRINGEMENT OR THE LIKE, unless expressly set forth herein.