

CAST PTFE FILM FOR CHEMICAL, THERMAL AND MECHANICAL APPLICATIONS

Cast Film™ Bondable Products:

TCI has a cast fluoropolymer film product line that consists of a 100% PTFE film with a surface treatment / modification for adhesive bonding and /or lamination to various substrates.

Several colors and surface treatments are available.

Variations Available:

- Various surface modifications and treatments
- Available un-pigmented (natural/clear)
- Available pigmented in colors including red, blue, white, yellow & tan



BONDABLE CAST PTFE FILM PRODUCTS PROPERTIES

Weight Conversion (lbs to sq ft): One pound of 1 mil film yields 90 sq ft

Thickness Range inches (mm): 0.001" to 0.005" (0.0254 mm to 0.127 mm

Maximum Width: inches (mm) 55" (1400mm)

Service Temperature: °F (°C) -328 to 400 (-200 to 205)

Tensile Strength, typical* (psi): 4800

Elongation, minimum (%): 400

Surface Tension, minimum (dynes): 40

*0.002" (50 µm) film

This information is supplied in good faith and is based on information currently available. TCI makes NO WARRANTIES, EITHER EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTIES FOR FITNESS, OR USE FOR A PARTICULAR PURPOSE, OR OF ANY MERCHANTABILITY OR AGAINST INFRINGEMENT OR THE LIKE, unless expressly set forth herein.

TEXTILES COATED INTERNATIONAL | Manufacturer of High-Performance Fluoropolymer Films, Laminates, and Composites