




SILVERJAC™ 3200 Insulation Jacketing Material

SILICONE/FIBERGLASS COMPOSITES ENGINEERED FOR REMOVABLE INSULATION SERVICE

SILVERJAC™ 3200 Description:

This silicone/fiberglass composite with a proven flexible coating is engineered for heavy duty insulation jacketing applications.

- **Successfully used in insulation jacketing service since 1985**
- **Incorporates proven SILVERJAC coating technology**
- **Severe chemical and temperature exposure capabilities**



Product Close-up

- **Variations available upon request**
- **Flame-resistant**
- **Easily sewn**

SILVERJAC™ 3200 PROPER-

Upper Use Temperature:	480°F (249°C) Continuous Service
Weight:	34.0 oz/yd ² (1153 g/m ²)
Thickness:	0.030" (0.76 mm)
Width:	59.5" (1511.3 mm) Nominal
Tensile Strength (Warp):	425 lbs/in (3719 N/50 mm)
Tensile Strength (Fill):	360 lbs/in (3150 N/50 mm)

SILVERJAC is a trademark of TEXTILES COATED INTERNATIONAL. Patents worldwide. This information is supplied in good faith and is based on information currently available. TCI makes NO WARRANTIES, EITHER EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTIES FOR FITNESS, OR USE FOR A PARTICULAR PURPOSE, OR OF ANY MERCHANTABILITY OR AGAINST INFRINGEMENT OR THE LIKE, unless expressly set forth herein.

TEXTILES COATED INTERNATIONAL | Manufacturer of High-Performance Fluoropolymer Films, Laminates, and Composites

200 Bouchard Street, Manchester, NH 03103 USA PHONE: (603) 296-2221 FAX: (603) 296-2248 www.textilescoated.com