



TEXFILM™ 402/2 Expansion Joint Material

LAMINATED PTFE/FIBERGLASS COMPOSITES ENGINEERED FOR MODERATE FLUE GAS SEAL SERVICE

TEXFILM™ 402/2 Expansion Joint Material:

TEXFILM™ 402/2 is a nonporous composite consisting of a PTFE-coated fiberglass fabric and CrossFilm™ barriers, which have been laminated to both sides of the fabric.

A durable PTFE coating has been applied to a rugged, continuous-filament fiberglass reinforcement. Three plies of high strength PTFE film were laminated to produce each of the CrossFilm™ barriers. The resulting 0.003 in (0.08 mm) thick PTFE barriers are rugged, flexible, and stress crack resistant.

This cost-effective expansion joint material has been engineered for light-to-moderate duty flue gas service.



- **TEXFILM™ has been successfully used in expansion joint service since 1990**

- **Proven coating and lamination technology for industrial fabrication**
- **Severe chemical and temperature exposure capabilities**
- **Product variations available upon request**

TEXFILM™ 402/2 PROPERTIES

Upper Use Temperature:	600°F (316°C) Continuous
Overall Weight:	27 oz/yd ² (918 g/m ²)
Thickness:	0.021 inches (0.52 mm)
Width:	60 inches (1524 mm) Nominal
Tensile Strength (Warp):	500 lbs/in (4378 N/50 mm)
Tensile Strength (Fill):	350 lbs/in (3065 N/50 mm)

TEXFILM™ and CrossFilm™ are trademarks of Textiles Coated International. This information is supplied in good faith and is based on information currently available. TCI makes NO WARRANTIES, EITHER EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTIES FOR FITNESS, OR USE FOR A PARTICULAR PURPOSE, OR OF ANY MERCHANTABILITY OR AGAINST INFRINGEMENT OR THE LIKE, unless expressly set forth herein.

TEXTILES COATED INTERNATIONAL | Manufacturer of High-Performance Fluoropolymer Films, Laminates, and Composites

200 Bouchard Street, Manchester, NH 03103 USA PHONE: (603) 296-2221 FAX: (603) 296-2248 www.textilescoated.com